TECHNIC, INC. MATERIAL SAFETY DATA SHEET

SECTION 1

PRODUCT IDENTIFICATION

TRADE NAME (AS LABELED): TECHNI NICKEL HT-2 RTU

CHEMICALS NAMES. COMMON NAMES:

PRODUCT CODE: 130709

MANUFACTURE S NAME & ADDRESS:

PREPARED BY: ALLAN H. REED

TECHNIC INC.

1 SPECTACLE STREET CRANSTON, RI 02910

DATE PREPARED: August 2, 2013

EMERGENCY PHONE: 401-781-6100

24 HOUR EMERGENCY: CHEM TREC 800-424-9300 OUTSIDE THE USA AND CANADA: 703-527-3887

SECTION 2	COMPOSITION / INFORMATION ON INGREDIENTS			
CHEMICAL NAMES	CAS NUMBER	PERCENT	EXPOSURE LIMITS	
Nickel sulfate	10101-97-0	8-12%	0.1 mg/m ³ (Ni) ACGIH TWA 1 mg/m ³ (Ni) OSHA PEL	
Boric acid	10043-35-3	2-5%	10 mg/m ³ ACGIH TLV 5 mg/m ³ OSHA PEL	
SECTION 3	HAZARD IDEN	NTIFICATION		

SYMPTOMS OF OVER-EXPOSURE FOR EACH POTENTIAL ROUTE OF EXPOSURE.

INHALATION:

Vapor or mist may be slightly irritating to nasal and respiratory

passages.

CONTACT WITH SKIN OR EYES: Will cause minor skin irritation (nickel itch); will cause irritation and

burns to eyes.

ABSORBED THROUGH SKIN:

Not readily absorbed through unbroken skin.

SWALLOWED:

Will cause irritation to membranes of mouth, throat, esophagus and

stomach. May cause gastric upset including nausea, vomiting and

diarrhea.

YES (IARC,NTP) SUSPECTED CANCER AGENT?

PAGE 2 OF 4

PRODUCT: TECHNI NICKEL HT-2 RTU

HEALTH EFFECTS OR RISKS FROM EXPOSURE. EXPLAIN IN LAY TERMS.

ACUTE: Individuals sensitive to nickel may develop allergic dermatitis (nickel itch) and asthma, bronchitis or wheezing.

CHRONIC: Nickel compounds are reported carcinogens.

SECTION 4

FIRST AID MEASURES

FIRST AID: EMERGENCY PROCEDURES

EYE CONTACT: Flush with water, including under lids, for fifteen minutes. Obtain immediate medical attention.

SKIN CONTACT: Remove contaminated clothing and wash affected area thoroughly with soap and water. Launder clothing before rewearing. Seek medical attention for prolonged skin irritation.

INHALED: Remove patient to fresh air. Support breathing if required. Obtain medical treatment for dizziness, unconsciousness or irritation or difficulty in breathing.

SWALLOWED: If patient is conscious, rinse mouth and drink at least two large glasses of water. DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Obtain immediate medical attention.

SECTION 5

FIRE FIGHTING MEASURES

FLASH POINT (°F) (METHOD USED): N.A. (Does not burn)				
AUTOIGNITION TEMPERATURE, °F: N.A.				
FLAMMABLE LIMITS IN AIR, VOLUME, %: LOWER LIMIT N.A. UPPER LIMIT N.A.				
FIRE EXTINGUISHING MATERIALS: Use media appropriate for the surrounding fire.				
WATER CARBON DIOXIDE OTHER				
FOAM DRY CHEMICAL				
SPECIAL FIREFIGHTING PROCEDURES: Wear approved self-contained breathing apparatus and full protective gear.				

UNUSUAL FIRE AND EXPLOSION HAZARDS: May emit toxic fumes under fire conditions.

SECTION 6

ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear protective gear. Contain spilled material and collect by absorption or other suitable method for disposal. Do not allow this material to enter storm or sanitary sewers or other waterways.

PAGE 3 OF 4

PRODUCT: TECHNI NICKEL HT-2 RTU

SI	EC	TIC	M	7

HANDLING AND STORAGE

HANDLING AND STORAGE REQUIREMENTS:

Store in a cool, dry place. Keep container tightly closed except when transferring material.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

VENTILATION:

Local exhaust.

RESPIRATORY PROTECTION:

Wear approved respirator when ventilation is inadequate to meet

exposure limits.

EYES PROTECTION:

Chemical splash goggles.

GLOVES:

Rubber.

OTHER CLOTHING AND EQUIPMENT: Rubber apron and long sleeves.

WORK PRACTICES, HYGIENIC PRACTICES: Wash hands thoroughly with soap and water after handling and before eating or smoking.

SECTION 9

PHYSICAL / CHEMICAL PROPERTIES

VAPOR DENSITY (AIR =1):

N.D.

SPECIFIC GRAVITY @ 25 °C: 1.18 +/- 0.05

VAPOR PRESSURE (MM Hg): N.D.

MELTING POINT (°F): N.D.

EVAPORATION RATE (BUTYL ACETATE=1): N.D.

BOILING POINT (°F): >212° F

SOLUBILITY IN WATER:

Complete

pH, neat:

3.0-4.0

APPEARANCE AND ODOR:

Clear, green liquid; odorless.

SECTION 10

STABILITY AND REACTIVITY

STABILITY:

X STABLE

UNSTABLE

CONDITIONS TO AVOID: None.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids and oxidizing materials.

HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): Nickel residues

and oxides of sulfur.

HAZARDOUS POLYMERIZATION:

MAY OCCUR

X WILL NOT OCCUR

PAGE 4 OF 4

PRODUCT: TECHNI NICKEL HT-2 RTU

SECTION 11

TOXICOLOGICAL INFORMATION

ACUTE EFFECTS:

See section 3.

IRRITATION DATA:

See section 3.

TOXICITY DATA:

Oral LD50: 275 mg/kg (rat, nickel sulfate)

TARGET ORGAN DATA:

See section 3.

SECTION 12

ECOLOGICAL INFORMATION

No specific data; however, this material should be considered as harmful to aquatic life.

SECTION 13

DISPOSAL CONSIDERATIONS

Dispose of all chemical wastes at an appropriate waste disposal facility. Follow all local, state, and federal regulations for disposal of waste chemicals.

SECTION 14

TRANSPORT INFORMATION

Not regulated by DOT (road, rail), IMDG (sea) or IATA/ICAO (air).

SECTION 15

REGULATORY INFORMATION

This product is regulated as a toxic chemical under Section 313 of Title III/SARA, and 40 CFR, Part 372. This product is regulated by the California Proposition 65 list.

All ingredients are listed in the TSCA inventory.

For the purposes of the New Jersey Right to Know Law, the contents are partially known.

SECTION 16

OTHER INFORMATION

Н	
Health	2
Flammability	0
R	
Reactivity	0
Personal	
Protection	C